



Winkelprofil Nr. 277, 15 x 15 mm

- Aluminium.
- Selbstklebend.

TÜV Zertifikat-Nr. 44 780 14206214

Werkstoff:	EN AW 6063 (DIN EN 573)
Werkstoffzustand:	T6 (DIN EN 755-2)
Vorbehandlung:	E6 (DIN EN 17 611)
Schichtdicke Eloxal:	Klasse 15 (DIN EN 17 611)
Pulverbeschichtung:	optional (RAL-Farbtöne)

Geeignet für: Designbelag / LVT Click und Loose Lay, Designbelag / LVT Dryback, Laminat / Multilayer

Montageart: Kleben

Länge: 270 cm

Farben: silber, Edelstahl matt, schwarz pulverbeschichtet (RAL 9005)

Winkelprofile sind ideal geeignet als kleiner Treppenwinkel, als Türschwellenprofil oder als Abschluss an Podesten. Sie schützen die Kanten des Bodenbelags dauerhaft.

Angle edge no. 277, 15 x 15 mm

- Aluminium.
- Auto-adhesive.

TÜV certification no. 44 780 14206214

Material:	EN AW 6063 (DIN EN 573)
Material condition:	T6 (DIN EN 755-2)
Pre-treatment:	E6 (DIN EN 17 611)
Thickness of anodised layer:	Class 15 (DIN EN 17 611)
Powdercoating:	optional (RAL-hues)

Suitable for: Design flooring / LVT click and loose lay, Design flooring / LVT dryback, Laminate / multilayer

Installation: gluing

Length: 270 cm

Colours: silver, stainless steel matt, black powdercoated (RAL 9005)

Angle edges are ideally suited as a small staircase angle, as a door threshold profile or as a termination on platforms. They protect the edges of the flooring permanently.